

# XR630-A



**A** CLASS  
CARRIAGE

**COMPACT**  
BOOM

## SPECIFICATIONS

Lift capacity	6,000 lbs
Max lift height	30' 7"
Forward reach	18' 5"
Frame leveling L/R	6°
Weight*	13,700 lbs
Engine (Deutz)	2.9L 74hp – T4F
Axles	Comer S128
Transmission	Linde HPV 055
Fuel capacity	26 gal
Tires	12 x 18 R4 pneumatic
Hydraulic flow (gpm)	21.5 gal
Hydraulic pressure	3,200 psi
Hydraulic oil capacity	55 gal
Length to fork face	16' 3"
Width	78"
Height	7'
Wheelbase	116"
Ground clearance	13.25"
Turning radius	11'

\*Weight based on open cab model with foam-filled tires.

## STANDARD FEATURES

- 360° operator visibility
- Easy service access
- Steel hydraulic & fuel tank
- Melonite pins
- Plastic fenders
- Plastic dash with display screen
- Linde hydrostatic 2-speed transmission
- Easy cab-mounted grab handles
- Large cross section boom
- Solid steel plate chassis
- Limited-slip front & rear axle
- Tier 4 final compliant engine
- Machine lift points

## LOAD CAPACITY CHART

Load ratings shown are for vehicles equipped with air-filled, foam-filled or solid tires. Load includes weight of any rigging. 3,000 lbs. at 24" minimum capacity/fork (6,000 lbs./pair).

